



Interlam BioMatt 75µ (2.9 mil)

Product Description

Interlam BioMatt 75µ is a 50µ (2.0 mil) bio-degradable matt overlaminating film coated on one side with a pressure sensitive, aqueous acrylic adhesive which is protected by a 36µ Clear Polyester film release liner, one side being siliconised for easy release.

Available in various sizes.

As the film is fully bio-degradable after use it can be disposed of in the normal waste channels.

Suggested Applications

Interlam BioMatt is recommended for situations where a non-glare finish is required or where specific lighting conditions cannot be controlled. It is ideal for images such as exhibitions and pop-up displays that will be viewed under direct lighting from many different angles.

Product Structure

Film:	50µ Bio-degradable matt film	
Adhesive:	Aqueous Acrylic (Pressure Sensitive)	
Release Liner:	36µ Clear Polyester film release liner	

General Properties

Film Thickness	50µ (2.0mil)
Adhesive Layer	25µ (1mil)
Ratio Film/Adhesive	2/1
UV Protection Factor	n/a

Outdoor Durability Not Applicable

Heat resistance 100°C (212°F) maximum

Peel Strength (20 min, FTM1) 23 N/25mm

Process Settings

Roller Laminator Temperature: Room temperature to 49°C (120°F) Speed: 0.3m to 1.75m (1 ft to 6 ft) per minute	Press NOT RECOMMENDED
--	---------------------------------

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660
 Drytac Corp. (USA) – 5383 Glen Alden Drive, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610
 Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Telephone: 1-800-353-288