



Protac Scribe™ UV 62μ (2.4 mil)

Product Description

Protac Scribe™ 62μ (2.4 mil) is a 40μ (1.6 mil) gloss finish, biaxially oriented polypropylene (BOPP) overlaminating film coated on one side with a pressure sensitive, acrylic adhesive, which is protected by a bleached Kraft release paper (moisture stable) coated on both sides with polyethylene and siliconised on the release side. Available in various sizes.

Suggested Applications

Protac Scribe™ cold laminating film is ideally suited for application to heat-sensitive output and high ink coverage prints printed on photo gloss paper. The most common demands for these products are for reusable presentation boards, schedules, year planners and maps.

Product Structure

Film:	Dry-erase/gloss Polypropylene (BOPP) film	62μ (2.4 mil)
Adhesive:	Acrylic (Pressure Sensitive)	
Release Liner:	2 Side PE Coated Bleached Woodfree Paper (Moisture Stable)	

General Properties

Film Thickness	40μ (1.6 mil)
Adhesive Layer	22μ (1mil)
Ratio Film/Adhesive	1.8/1
UV Protection Factor	Film contains some U.V. stabilisers, which prevent film degradation, but should be used for indoor applications only.

Heat Resistance Range	110oC to 120oC (230oF to 248oF)
Peel Strength (20 min, FTM1)	12 N/25mm

Process Settings

Roller Laminator	Press
Temperature: Room temperature to 49°C (120°F) Speed: 0.3m to 2.1m (1 ft to 7 ft) per minute	NOT RECOMMENDED

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660

Drytac Corp. (USA) – 5383 Glen Alden Drive, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610

Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Telephone: 1-800-353-288