



Dry Mount Film

Product Description

Dry Mount Film is an a 50µ (2 mil) plasticised, clear PVC mounting film coated on both sides with a heat activated solvent acrylic adhesive, which is protected on both sides by bleached Kraft grey grid release paper coated on one side with siliconised polyethylene. Available in various sizes.

Suggested Applications

Dry Mount Film is suitable for mounting to canvas, heavily grained or textured substrates and most other irregular surfaces, including most metals.

Product Structure

Release Liner:	1 Side PE coated bleached Kraft Grey Grid Paper (Moisture Stable)	
Adhesive:	Solvent Acrylic (Heat Activated)	
Carrier:	Clear PVC	
Adhesive:	Solvent Acrylic (Heat Activated)	
Release Liner:	1 Side PE coated bleached Kraft Grey Grid Paper (Moisture Stable)	

General Properties

Film Thickness	50µ (2 mil)
Adhesive Layer	25µ (1 mil) on each side
Ratio Film/Adhesive	1/1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Heat resistance	70°C to 95°C (158°F to 203°F)

Process Settings

Roller Laminator NOT RECOMMENDED	Press Temperature range: 85°C to 100°C (185°F to 212°F) Dwell time: 60 to 90 seconds
--	---

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660
Drytac Corp. (USA) – 5383 Glen Alden Drive, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610
Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Telephone: 1-800-353-288