



Dry Mount Film White

Product Description

Dry Mount Film White is an 80µ (3.2 mil) plasticised, white PVC mounting film coated on both sides with a heat activated solvent acrylic adhesive, which is protected on both sides by bleached Kraft red grid release paper coated on one side with siliconised polyethylene. Available in various sizes.

Suggested Applications

Dry Mount Film White is particularly suitable for mounting prints or graphics which are light coloured, are transparent or have a low colour coverage to canvas, board (particularly dark board), heavily grained or textured substrates and most other surfaces including most metals.

Product Structure

Release Liner:	1 Side PE coated bleached Kraft Red Grid Paper (Moisture Stable)	
Adhesive:	Solvent Acrylic (Heat Activated)	
Carrier:	White PVC	
Adhesive:	Solvent Acrylic (Heat Activated)	
Release Liner:	1 Side PE coated bleached Kraft Red Grid Paper (Moisture Stable)	

General Properties

Film Thickness	80µ (3.2 mil)
Adhesive Layer	25µ (1 mil) on each side
Ratio Film/Adhesive	1.6/1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Heat resistance	70°C to 95°C (158°F to 203°F)

Process Settings

Roller Laminator NOT RECOMMENDED	Press Temperature range: 79°C to 100oC (175oF to 212oF) Dwell time: 60 to 90 seconds
--	---

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660
 Drytac Corp. (USA) – 5383 Glen Alden Drive, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610
 Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Telephone: 1-800-353-288