



Facemount™ UV

Product Description

Facemount™ UV is an optically clear UV stable pressure-sensitive mounting adhesive protected on each side by a 25µ clear polyester release liner.

Suggested Applications

Facemount™ UV is engineered for the face mounting of virtually any image to clear substrates like PetG™, Acrylic, Plexiglas™ and Polycarbonate. Facemount is also appropriate for lenticular imaging applications and backlit display transparencies.

Product Structure

Release Liner:	One side siliconised polyester
Adhesive:	Solvent Acrylic (Pressure Sensitive) - UV Stabilised
Film:	Clear polyester
Adhesive:	Solvent Acrylic (Pressure Sensitive) - UV Stabilised
Release Liner:	One side siliconised polyester

General Properties

Film Thickness	25µ (1 mil)
Adhesive Layer	25µ (1 mil) on each side
Ratio Film/Adhesive	1/2
UV Protection Factor	The adhesive contains UV stabilisers to ensure no yellowing of adhesive and gives some protection to the underlying image.
Outdoor Durability	N/A
Heat resistance	-46°C to +135°C (-50°F to +275°F)
Peel Strength (20 min, FTM1)	8.8 N/25mm

Process Settings

Roller Laminator	Press
Temperature: Room temperature to 49°C (120°F) Speed: 0.3m to 1.25m (1 ft to 4 ft) per minute	NOT RECOMMENDED

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660
Drytac Corp. (USA) – 5383 Glen Alden Drive, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610
Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Telephone: 1-800-353-288