



## FEATURES

- Compact footprint
- Automated start-up and shut down
- Variable speed control up to 43 feet/minute (13 meters/minute)
- Separate pump and filter for 2 coatings plus wash
- Swing out side panels allow easy access to rollers and components.
- Casters with leveling feet
- Great for coating photos and UV printed output
- Pre coat ceramic tiles, aluminum and glass.
- Variable speed peristaltic pumps
- High quality industrial design with digital control panel
- CE compliant
- 1" nip opening

# DRYTAC®

## EXPERTS IN FINISHING SOLUTIONS

### A multiple purpose 24" coater

More compact and at a lower price point than the large format VersaCoater™ XL, the VersaCoater™ MultiPro delivers a similar coating quality and is perfect for print shops with limited space wanting to add UV curable coating capabilities or larger print shops wanting a UV coater for smaller jobs. The MultiPro can add a durable gloss, matte or lustre finish to printed graphics from most high-end digital color printers. Printed ceramic tiles, aluminum sign blanks, printed vinyl decals, maps, photos, menus, posters, postcards and point-of-purchase displays can all be coated with this machine.

### Versatile features make the MultiPro usable for a variety of jobs

With its adjustable nip opening, the VersaCoater™ MultiPro is able to coat output printed on multiple types of materials from 2 mil Sintra™ to substrates up to 1 inch thick. Dynamic Coating Technology with independently adjustable top and bottom rollers enables you to coat uneven textured materials such as canvas and wall coverings. The VersaCoater™ MultiPro is also compatible with traditional offset litho, digital press and photographic output with the standard coating roller.

### Easy to use and maintain

Designed with ease of use and maintenance in mind, the VersaCoater™ MultiPro features four swing out side panels to allow easy access to the rollers, curing station and other working parts for cleanup and maintenance. Three supply tanks accommodate two different coatings plus a cleaning solution; adjustable coating thickness controls and automated start-up and shut down all make this coater a breeze to use and maintain. A high efficiency drain pan and selectable coating tanks allow for use of specialty coatings, including TexCoat and pigmented coatings.

## TECHNICAL SPECIFICATIONS—VERSACOATER™ MULTIPRO

### Coating Specifications:

Max. Coat Width:	24" (609 mm)
Coating Capacity:	0.5 U.S. Gallon (0.416 U.K. Gallon) / coats up to 1500 sq ft (139 sq meters)
Substrate Thickness (min-max)	2 mil to 1" (25 mm) thick
Coating Technology:	100% UV curable - reverse roll / flood
Coating Roller:	Proprietary EDPM/silicon blend
Available Finish:	Gloss, Lustre, Matt

### Speed and Dimensions:

Process Speed:	10 - 43 feet/minute (3 - 13 meters/minute)
Coater Size: (L x W x H):	68" (1727 mm) x 51" (1295 mm) x 51" (1295 mm)
Crated Size: (L x W x H):	88" (2235 mm) x 24" (609 mm) x 30" (762 mm)
Coater Net Weight:	160 lbs (72.5 Kg)
Crated Weight:	400 lbs (181.5 Kg)

### Electrical Specifications:

Line Voltage (Europe):	50Hz, 3 phase Y, 380 Volts, 30 Amps (does not include cord)
Line Voltage (North America):	60Hz, 1 phase, 220 Volts, 30 Amps (does not include cord)

### Safety and Warranty:

Safety Certification:	CE Compliant
Emergency Shut Off:	Yes
Ventilation:	External ventilation or air purification highly recommended
Warranty:	

### Order Codes:

Coater	VC-MP24
--------	---------

### Compatible InstaCure UV Curable Coatings:

Direct mail, brochures and menus	Digital Gloss, ICUVCDG
	Digital Matte, ICUVCDM
Floor graphics	EmeryCoat Anti-Slip, ICUVECAS
Point of Purchase displays	POP, ICUVPOP
Hard-to-print substrates	Primer Coat Clear, ICUVPCC
All purpose jobs	Variable Gloss, ICUVVG
Reverse printed graphics	Superflex White, ICUVSFW



US TOLL FREE 1-800-280-6013  
CANADA TOLL FREE 1-800-353-2883

ON THE WEB:  
[www.drytac.com](http://www.drytac.com)

RevMar2310