

WindowTac

Product Description

A 23mic (1mil) visually clear PET film with a permanent adhesive on one side and a removable adhesive on the other. This double sided mounting adhesive is designed for easy, bubble-free facemounting of large graphics to glass or clear acrylic* panels with the aid of a squeegee.



Applications

This product has a variety of applications ranging from POP displays, promotional graphics, back-lit display cabinets, shop fronts, and anywhere that requires short term removable facemounted displays.

Directions for use:

1. Ensure windows are cleaned thoroughly with soap and water, 2 drops into 3 litres of water, and ensure it is completely dry before any application of the product is done.
2. Laminate the permanent adhesive to the face side of the image.
3. Remove the embossed release liner and apply by hand using a squeegee with minimum pressure.
4. The micro grooves imparted into the adhesive layer by the embossed release allow the air to evacuate upon installation, giving a bubble-free, easy application.
5. The image can be repositioned up to ten times whilst retaining the micro grooves.
6. Allow the images to cure for 24 hours for the adhesion to increase.

*If using clear acrylic sheets, ensure that the material has been thoroughly cured to reduce the risk of "out gassing".

General Properties

Film thickness	23µ (1mil)
Heat resistance range	70° C (158° F)
Peel strength (20 min, FTM1)	22N/25mm2 (PERM)

Roller Laminator (Not to be used with a Vacuum Press)

Temperature	Room temperature to 15-27° C (40 - 65% humidity)
Speed	0.3m to 1.75m (1ft to 6ft)/min

Product Code

Size

PWD25082	650mm X 25m
PWD41164	1040mm X 50m
PWD51164	1300mm X 50m



DRYTAC®

Tel +44 (0)117 958 6500
0845 070 0660
Email bristol@drytac.com
Web www.drytac.com