



TransferTac™

Product Description

TransferTac™ is a pressure sensitive, aqueous acrylic, mounting adhesive, which is protected by a bleached Kraft differential release paper (moisture stable) coated on both sides with siliconised polyethylene. Available in various sizes.

Suggested Applications

TransferTac™ is recommended for use with flexible and/or rollable substrates such as banner materials and PVC (vinyl) substrates

Product Structure

Adhesive:	Aqueous acrylic
Release Paper:	2 Side PE Coated Bleached Kraft Differential Release Paper (Moisture Stable)

General Properties

Film Thickness	N/A
Adhesive Layer	25mic (1mil)
Ratio Film/Adhesive	N/A
UV Protection Factor	N/A

Outdoor Durability 6 months will only show inconsequential changes in properties of this product.

Peel Strength (20 min, FTM1) Substrate dependant

Process Settings

Roller Laminator	Press
Temperature: Room Temperature to 49°C (120°F) Speed: 0.3m to 2.5m (1 ft to 8 ft) per minute	NOT RECOMMENDED

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660
Drytac Corp. (USA) – 5383 Glen Alden Drive, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610
Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Telephone: 1-800-353-288

<http://www.drytac.com>