

# Sheet Fed Roller Coater PhotoCoater CS



## 24" Format

Is your current sheet fed roll coater giving you fits? Tired of plastic gears that keep breaking? Wouldn't it be nice to know you actually got what you paid for in a liquid coater?

## Your wait is over . . .

The PhotoCoater CS aqueous based sheet fed roll coater is the perfect and easy way to coat photographs, printed self adhesive decals and much more . . . Coating costs range from 4 cents to 11 centers per square foot depending on the application and coating used.

## Coat your prints "face up"

The PhotoCoater CS is easy to operate. Compatible with sheet fed prints up to 30 mils thick, the PhotoCoater CS has a fully adjustable nip, temperature and and speed controls. Running prints is as simple as three easy steps.

1. Set speed and temperature on the convenient control panel
2. Adjust the nip and pour in coating
3. Press start switch and feed prints

## Easy to clean

At the end of your production day, simply squirt the roller assy with cleaning fluid, let run for approximately five minutes, then open rollers to allow mixture to fall into tray below. Pat the rollers dry or let the rollers run until dry.

## Available Sizes

The PhotoCoater CS comes in 24-inch (61cm) coating widths.

## FEATURES

- Infrared heating for high throughput
- Metal gears and chain
- Flip-up cover for easy access to rollers
- Automatic temperature control
- Variable speed control
- Cooling fans at take up
- Separate run and clean modes
- Textured rollers available

**DRYTAC**<sup>®</sup>

## TECHNICAL SPECIFICATIONS

### SHEET FED ROLLER COATER

**24" (60.96cm)**

#### Coating Specifications:

Max. Coat Width:	24" (60.96cm)
Max Coating Thickness:	5 microns (.20 mil)
Coating Technology:	
Available Finish:	Semi Smooth (E Surface)

#### Speed and Dimensions:

Process Speed:	
Coater Size: (L x W x H):	30" x 35" x 18 (76cm x 89cm x 46 cm)
Crated Size: (L x W x H):	33" x 38.5":x 21" (84cm x 98cm x 117 cm)
Coater Net Weight:	100 lbs (45.4 kg)
Crated Weight:	160 lbs (72.5 kg)

#### Electrical Specifications:

Line Voltage:	120 VAC - 50/60Hz
Power Consumption	750 Watts
Amperage:	17 amps (20 amp circuit) single phase

#### Safety and Warranty:

Safety Certification:	CE Standards
Warranty:	1 year parts

#### Order Codes:

Coater & Curing Unit	#WBPC-24
----------------------	----------

## INSTACURE LIQUID COATINGS

**NOTE:** This coater is not intended for graphics subjected to heavy use, abrasion or chemical exposure. These applications require the use of a UV curable or aqueous based flood coater such as the VersCoater™ XL or the AFC1600.

The logo for DRYTAC, featuring the word "DRYTAC" in a bold, red, sans-serif font. A horizontal line is drawn through the middle of the letters, creating a stylized effect.

**US TOLL FREE 1-800-280-6013**  
**CANADA TOLL FREE 1-800-353-2883**

**ON THE WEB**  
[www.drytac.com](http://www.drytac.com)