
ViziPrint®

Illuminate

ViziPrint[®] Illuminate is a high quality, translucent matte PET film with a halide coating for enhanced illuminated backlit displays that uses a mechanical bond to adhere graphics to glass and other smooth, flat surfaces. Thanks to its hybrid adhesive technology, no adhesive residue is left behind during graphic removal. The film is very durable and does not require overlamination for graphics. Additionally, its bright white base color and ability to diffuse light creates brighter, more vivid window images that have a wider color gamut. ViziPrint[®] Illuminate is reverse printable, allowing for indoor and outdoor visibility of window graphics. It is ideal for window advertisements viewed during the day in direct sunlight or illuminated at night by store lighting. It can also be used for privacy and decorative glass applications as well as backlit displays.

- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

Product Code: VPIL



DISPLAYS VIVID GRAPHICS DAY & NIGHT





APPLICATIONS

Smooth Flat Surfaces Retail & Backlit Applications

Window Graphics

Decals & Stickers

Certified for HP Latex Inks





ViziPrint[®]

Illuminate

ViziPrint[®] Illuminate is a 100µ (4 mil) high quality, translucent matte PET film with a halide coating that uses a mechanical bond to adhere graphics to glass and other smooth, flat surfaces. With its hybrid adhesive technology, no adhesive residue is left behind during graphic removal. The film is very durable and does not require overlamination for graphics. ViziPrint[®] Illuminate is reverse printable, allowing for indoor and outdoor visibility of window graphics. Its bright white base color and ability to diffuse light creates brighter, more vivid window images that have a wider color gamut.

- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- DIFFUSES LIGHT CREATING BRIGHTER VIVID IMAGES
- REVERSE PRINTABLE FOR INSIDE MOUNTING OF WINDOW ADVERTISEMENTS

INSTALLATION RECOMMENDATION

Wet or dry installation will work for ViziPrint® Illuminate. Please see ViziPrint® Illuminate installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information,

performance and warranty guide

lines please contact your local

Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Translucent Matte PET
Adhesive	Hybrid Adhesive Technology
Release Liner	Siliconized 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ)
Outdoor Durability	6 months
Application Temperature	>23°F (-5°C)
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PRINTING RECOMMENDATIONS

- Printing temperature should be 59-
- 86°F (15-30°C) with 30-60% humidity.
 Set printer to highest print setting for
- optimal print quality.
- If mounting on glass or backlit substrates, evaluate color density of the print on a window or in transmitted light.



Europe

Filwood Road, Fishponds, Bristol, BS16 3RY, United Kingdom bristol@drytac.com Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court, Brampton, Ontario, L6T 5A9, Canada toronto@drytac.com Tel: +1 800.353.2883 USA

5601 Eastport Boulevard, Richmond, Virginia, 23231, USA customerservice@drytac.com Tel: +1 800.280.6013

www.drytac.com