

# ReTac®

## Smooth 150

Our 6 mil (150 $\mu$ ), white polymeric printable PVC film with ReTac® ultra removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned.

Dimensionally stable, ReTac® Smooth 150 can be applied and re-positioned multiple times without stretching or tearing. And, with ReTac® on the back, you never have to worry about adhesive setting up, being left behind, or damaging the surface it is adhered to when graphics are removed.

- IDEAL FOR INTERIOR WALL GRAPHIC APPLICATIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

**6** mil White Phthalate-Free Polymeric PVC



Matte or Gloss



(Eco) Solvent  
Latex  
UV



ReTac® ultra removable  
and re-positionable  
adhesive



Widths up to 61 in



5 YEARS DURABILITY  
INTERIOR AND EXTERIOR  
(2 YEAR REMOVABILITY EXTERIOR)

### EASY APPLICATION AND REMOVAL



### APPLICATIONS

- Smooth Flat Surfaces
- Point Of Sale Graphics
- Interior Décor
- Decals & Stickers

Certified for  
HP Latex Inks



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# ReTac®

## Smooth 150

ReTac® Smooth 150 is a 6 mil (150 $\mu$ ) printable matte or gloss white, phthalate-free polymeric PVC film, coated on one side with ReTac® ultra removable adhesive. The adhesive is protected by a single-sided, siliconized PE coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. ReTac® Smooth 150 can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- PHTHALATE-FREE FILM
- IDEAL FOR REMOVABLE WALL DECALS, APPLIQUES AND WALL MURALS
- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, AND GLASS
- RETAC SMOOTH 150 HAS SEVERAL FIRE RATINGS, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal, for more information please contact your local representative.

**For more information,  
performance and warranty  
guidelines please contact your  
local Drytac office.**

© 2024 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.

05132022

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	Matte or Gloss White Polymeric PVC
Adhesive	ReTac® ultra removable and re-positionable adhesive technology
Release Liner	90# (146 gsm) 1 Side Siliconized PE Coated Kraft Paper

### PRODUCT CHARACTERISTICS

Film Thickness	6 mil (150 $\mu$ )	6.9 mil (172 $\mu$ )
Adhesive Layer	0.9 mil (22 $\mu$ )	
Outdoor Durability	5 years; 2 years removability	
Application Temperature	>41°F (5°C)	
Service Temperature Range	40°F to 120°F (4.4°C to 48.9°C)	
Fire Ratings	Class 0 (BS 476 - Part 6 & 7) Class C-s1, d0 (EN 13501-1) PASS (CAN/ULC-S102) Class A or 1 (ASTM E-84)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### OVERLAMINATE RECOMMENDATIONS

When using ReTac® Smooth 150, an overlaminant can be used for maximum life expectancy. Products recommended for use with ReTac® Smooth 150 are Drytac's Interlam™ Pro overlaminates.

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013