

Polar®

Grip

with Interlam™ Pro Emerytex®

Polar® Grip is a 3.2 mil (80µ) premium, white polymeric self-adhesive PVC film with a high coat weight, permanent, pressure sensitive grey acrylic adhesive that is protected by a 90# poly coated kraft release liner. The film's unique aggressive adhesive makes it suitable for graphic applications where flexibility and high bond adhesion are desired.

Interlam™ Pro Emerytex® is a 4 mil (100µ) monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

- IDEAL FOR INDOOR & OUTDOOR FLOOR GRAPHICS
- THE PAIRED SOLUTION CARRIES SEVERAL SLIP RATINGS & CERTIFICATIONS



Polar Grip
(Eco) Solvent
Latex
UV



Widths up to 54in



UP TO 12 MONTHS DURABILITY
INTERIOR & EXTERIOR*

* Up to 12 months durability dependent upon floor-traffic and correct installation.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

PAIRED FLOOR GRAPHIC SOLUTION TECHNICAL SPECIFICATIONS

Polar® Grip

PRODUCT STRUCTURE

Film Gloss or Matte White Polymeric PVC

Adhesive (Pressure Sensitive) High Coat Weight Grey Permanent Acrylic

Release Liner 90# Poly Coated Kraft

Polar® Grip

PRODUCT CHARACTERISTICS

Film Thickness 3.2 mil (80µ) | 4.6 mil

Adhesive Layer 1.4 mil (35µ) | (116.8µ)

Fire Ratings Class C -s1,d0 (EN 13501-1)
Class A or 0 (ASTM E-84)
PASS (CAN/ULC-S102)

Application Temperature >-4°F (-20°C)

Service Temperature Range -49°F to 230°F (-45°C to 110°C)

Interlam™ Pro Emerytex®

PRODUCT STRUCTURE

Film Matte Pebble Textured Monomeric PVC

Adhesive Acrylic (Pressure Sensitive)

Release Liner 2 Side PE Coated, 1 Side Siliconised Kraft

Interlam™ Pro Emerytex®

PRODUCT CHARACTERISTICS

Film Thickness 4 mil (100µ) | 5 mil

Adhesive Layer 1 mil (25µ) | (125µ)

Fire Ratings Class 0 (BS 476 Part 6 and 7)
Class 1 or A (ASTM E-84)

FDA Certification PASS (FDA 21 CFR 177.1975)

Slip Certifications Low Slip Potential (EN 13036-4)
R 11 (DIN 51130:2010)
Dry: 62; Wet: 35 (HB198:2014 (AS/NZS 4586))
Acceptable (ANSI B101.3)

Application Temperature >-4°F (-20°C)

Service Temperature Range -4°F to 203°F (-20°C to 95°C)

Polar® Grip & Interlam™ Pro Emerytex®

Paired Solution Fire Rating B₁ - s1
(EN 13501-1)

Shelf Life 1 year

Storage Conditions 59°F to 72°F
(15°C to 22°C);
50 - 55%

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com