

ReTac®

ChalkMate®

USE STANDARD CHALK OR LIQUID CHALK MARKERS

ReTac® ChalkMate® has a traditional black chalkboard finish that can be used with standard chalk or liquid chalk markers. It utilizes ReTac® ultra removable adhesive technology to create impromptu chalkboard walls that are easy to apply, re-position and remove without surface damage. It can be installed on most smooth surfaces. A second version is available that features a permanent, pressure sensitive acrylic adhesive, making it ideal for fixture applications. Both versions can also be used to make unique, custom chalkboard decals from die cut shapes or designs.

- IDEAL FOR INDOOR CHALK BOARDS
- SUITABLE FOR SCHOOLS
- CAN BE EASILY REPOSITIONED & REMOVED

5 mil
Black
Chalkboard
PVC

☐
Matte



Printers that use
white ink
UV



ReTac® ultra removable
and re-positionable
adhesive



Widths up to 61 in

DURABILITY
5
YEARS

INTERIOR & EXTERIOR

BBQ Grill Menu

Swiches	4.75
cken	6.20
tes	12.85
ubs	14.60
s	3.15
a Carte	21.45



• All Natural •



APPLICATIONS

CHALK BOARDS

RETAIL NOTICE BOARDS

MENUS & PRICE LISTS



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

ReTac® ChalkMate® is a 125µ (5 mil) durable, printable PVC film with a traditional black chalkboard finish and ReTac® ultra removable adhesive. ReTac® ChalkMate® can be easily applied, re-positioned and removed without surface damage or loss of adhesion. It works well when creating chalkboard walls or making unique, custom chalkboard decals from die cut shapes or designs. Installs on most smooth surfaces.

- IDEAL FOR IN STORE PROMOTIONS
- SUITABLE FOR INTERIOR & EXTERIOR USE, PLEASE NOTE WEATHER CONDITIONS MAY AFFECT YOUR CHALK.
- RETAC® CHALKMATE® HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal

**For more information,
performance and warranty guide
lines please contact your local
Drytac office.**

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Black PVC
Adhesive	ReTac® ultra removable and re-positionable adhesive
Release Liner	143 gsm 2 Side PE Coated, 1 Side Solventless Siliconised Fine Paper

PRODUCT CHARACTERISTIC

Film Thickness	5 mil (125µ)
Adhesive Layer	0.8 mil (20µ)
Film/Adhesive Ratio	5:0.8
UV Protection Factor	Not Applicable
Outdoor Durability	5 Years
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Flame Retardancy	Class 0 BS 476 - Part 6 & 7 Fire Rating
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

Special Regulatory Information:
This product is formulated to be compliant with the California Proposition 65 regulation. It contains no zinc, lead, cadmium, or other heavy metals. This product is formulated to be phthalate-free.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013