

ViziPrint®

Deco SR

This optically clear scratch-resistant printable window film utilises a special ink-receptive top coat for greater adhesion of inks. ViziPrint® Deco SR is ideal for architectural applications where decorative glass details are needed to create dynamic spaces, including conference rooms or private meeting areas. It can also be used to create graphics and window decals for retail storefronts and POP or backlit displays.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

Product Code: VPID

50
micron

Clear
Transparent
PET

☐
Gloss



UV
Latex



Clear
Permanent
Acrylic (Pressure Sensitive)



Width 1524mm

YEARS DURABILITY
7

INTERIOR

YEARS DURABILITY
3

EXTERIOR

CREATE ARCHITECTURAL APPLICATIONS

APPLICATIONS

Smooth Flat Surfaces
Retail Backlit Displays
Window Graphics
Decals & Stickers

Certified for
HP Latex Inks

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at hp.com/go/mediasolutionslocator



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Deco SR

ViziPrint® Deco SR is a 50µ (2 mil) scratch-resistant optically clear gloss PET film, coated with a permanent clear acrylic adhesive and protected by a siliconised PET release liner that has a super smooth profile to enhance the clarity when applied to glass. It has a special top coat to enhance the adhesion of inks. The film's high quality adhesive adheres to most substrates.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. Use gloves to avoid fingerprints. Wet installation is recommended.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Scratch-Resistant Gloss Transparent PET with Ink-Receptive Top Coat
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	2 mil (50µ)	2.8 mil (70 µ)
Adhesive Layer	0.8mil (20µ)	
Film/Adhesive Ratio	2:0.8	
UV Protection Factor	Not Applicable	
Outdoor Durability	3 Years	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 266°F (-20°C to 130°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013