

FloorTac® Plus

with Interlam™ Pro Emerytex®

ENGINEERED WITH NO-LIFT TECHNOLOGY

FloorTac™ Plus with Interlam™ Pro Emerytex® is designed for attention-grabbing floor graphics that instantly take floors from drab to fab. Its removable, non-damaging adhesive makes this paired solution ideal for short-term indoor advertising where graphics are applied to the floor. When combined with Drytac's Interlam™ Pro Emerytex® laminating films, FloorTac™ Plus provides a certified slip-resistant finish for the ultimate floor graphic solution.

CAN BE APPLIED TO:

- SHORT PILE CARPETS**
- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE, OR TERRAZZO

Product Code: PTU

190

micron
(Total Solution)

☐ Interlam Pro Emerytex
Matte Pebble PVC Film

☐ FloorTac Plus
Matte White PVC Film



FloorTac Plus

(Eco) Solvent
Latex
UV



Interlam Pro Emerytex
Pressure Sensitive Acrylic
Adhesive

FloorTac Plus
Removable Grey Acrylic
Adhesive



Widths up to 1524mm



INTERIOR*



APPLICATIONS

SCHOOLS
HOSPITALS
RETAIL ADVERTISING
SUPERMARKETS
RESTAURANTS



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

FloorTac[®] Plus

with Interlam[™] Pro Emerytex[®]

FloorTac[™] Plus is an 90μ (3.5 mil printable matte white monomeric PVC film with a removable, pressure sensitive grey acrylic adhesive protected by a 120 gsm siliconized 1 side white coated paper liner.

Interlam[™] Pro Emerytex[®] is a 4 mil (100μ) monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

● SUITABLE FOR MID TO HEAVY FOOT TRAFFIC AREAS

* Up to 9 months indoor durability dependent upon floor-traffic and correct installation.

**The carpet installation surface must be short pile or tightly woven, minimal texture with a limited cushion. The carpet should be clean and dry prior to application. Due to the huge variance of carpet surfaces, materials and types along with pre and post chemical treatments, a test sample is mandatory prior to production and installation. It is important that all printer and ink manufacturer guidelines are followed. The Drytac limited warranty only covers for material defect, no returns or consequential losses will be accepted.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

FloorTac[™] PRODUCT STRUCTURE

Film	Matte White Monomeric PVC
Adhesive	Removable Gray Acrylic (Pressure Sensitive)
Release Liner	120 gsm Siliconized 1 Side White Coated Paper

FloorTac[™] PRODUCT CHARACTERISTICS

Film Thickness	3.5 mil (90μ)	4.3 mil
Adhesive Layer	0.8 mil (20μ)	(110μ)
Application Temperature	>-4°F (-20°C)	
Service Temperature Range	-22°F to 302°F (-30°C to 150°C)	

Interlam[™] Pro Emerytex[®] PRODUCT STRUCTURE

Film	Matte Pebble Textured Monomeric PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 1 Side Siliconised Kraft

Interlam[™] Pro Emerytex[®] PRODUCT CHARACTERISTICS

Film Thickness	4 mil (100μ)	5 mil
Adhesive Layer	1 mil (25μ)	(125μ)
Fire Ratings	Class 0 (BS 476 Part 6 and 7) Class 1 or A (ASTM E-84)	
FDA Certification	PASS (FDA 21 CFR 177.1975)	
Slip Certifications	Low Slip Potential (EN 13036-4) R 11 (DIN 51130:2010) Dry: 62; Wet: 35 (HB198:2014 (AS/NZS 4586)) Acceptable (ANSI B101.3)	
Application Temperature	>41°F (20°C)	
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)	

Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC[®]
ADHESIVE SCIENCE

www.drytac.com