

# ViziPrint®

## Impress Clear SEL

Our optically clear printable window film is designed for trouble-free installation of graphics on glass surfaces. ViziPrint® Impress Clear utilises a low tack hybrid adhesive technology that creates a strong bond in both high and low temperatures without leaving residue behind. This adhesion technology also eliminates bubbling and is unaffected by moisture. Since it uses a mechanical bond to gently adhere images to windows, the glass stays clear and graphics stay bright whenever ViziPrint® Impress Clear is re-positioned and re-applied. The film is ideal for high quality decals, signage and retail window advertising.

- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

Product Code: VPI-SEL

**125**  
micron

Optically  
Clear  
PET



Gloss



(Eco) Solvent  
Latex  
UV



Hybrid  
Adhesive  
Technology



Widths up to 1524mm



3 YEARS DURABILITY  
INTERIOR



2 YEARS DURABILITY  
EXTERIOR\*

## BEAUTIFUL OPTICALLY CLEAR GRAPHICS



## APPLICATIONS

Smooth Flat Surfaces

Retail Displays

Window Graphics

Decals & Stickers



Certified for  
HP Latex Inks

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at [hp.com/go/mediasolutionslocator](http://hp.com/go/mediasolutionslocator)

# DRYTAC®

## ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# ViziPrint<sup>®</sup>

## Impress Clear

ViziPrint<sup>®</sup> Impress Clear is an optically clear PET film with hybrid adhesive technology that is protected by a clear, 1 side siliconised release liner. Its proprietary adhesion technology creates a strong bond in both high and low temperatures without leaving residue behind, eliminates bubbling and is unaffected by moisture. ViziPrint<sup>®</sup> Impress Clear can be re-positioned and re-applied multiple times, and removes cleanly up to 3 years after installation.

- IDEAL FOR APPLICATIONS ON GLASS AND OTHER SMOOTH, FLAT SURFACES *surfaces.*
- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- CAN BE USED ON ELECTRONIC EQUIPMENT, SUCH AS TV SCREENS, IPAD/TABLET DISPLAYS AND COMPUTER MONITORS, AS WELL AS REFRIGERATORS, GLASS DISPLAY CASES.
- REVERSE PRINTABLE FOR INSIDE MOUNTING OF WINDOW ADVERTISEMENTS.

### INSTALLATION

#### RECOMMENDATION

**Wet or dry installation will work for ViziPrint<sup>®</sup> Impress Clear. Please see ViziPrint<sup>®</sup> Impress Clear installation instructions for further details. The surface must be clean and smooth and free of defects before application.**

**For more information, performance and warranty guidelines please contact your local Drytac office.**

© 2022 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Optically Clear PET
<b>Adhesive</b>	Hybrid Adhesive Technology
<b>Release Liner</b>	Siliconized 1 Side PET

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	5 mil (125µ)
<b>*Outdoor Durability</b>	2 Years (ink dependent; see warranty for more details)
<b>Application Temperature</b>	>23°F (-5°C)
<b>Service Temperature Range</b>	-4°F to 248°F (-20°C to 120°C)
<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

#### PRINTING RECOMMENDATIONS

- Handle material with care prior to printing; use gloves to avoid finger prints.
- Printing temperature should be 59-86°F (15-30°C) with 30-60% humidity.
- Set printer to highest print setting for optimal print quality.  
If mounting on glass or backlit substrates, evaluate colour density of the print on a window or in transmitted light.

# DRYTAC<sup>®</sup>

## ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401 B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)