

Artshield™

Satinex

Artshield™ Satinex™ is a 2 mil (50µ) UV stabilized, pre-perforated clear PVC laminating film with a semi-gloss finish, coated on one side with a heat activated solvent acrylic adhesive that is protected by a moisture stable bleached Kraft gridded release paper coated on one side with siliconized PE.

- ENHANCES POSTERS, DIGITAL PRINTS AND PHOTOGRAPHS
- IDEAL FOR LAMINATING FABRICS AND CANVAS, AND PROTECTING RAISED SURFACES, SUCH AS LEAVES AND DRIED FLOWERS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Semi-Gloss Perforated PVC
Adhesive	Solvent Acrylic (Heat Activated)
Release Liner	1 Side PE Coated Bleached Kraft Grid Paper (Moisture Stable)

PRODUCT CHARACTERISTIC

Film Thickness	2 mil (50µ) 3 mil (75µ)
Adhesive Layer	1 mil (25µ)
Film/Adhesive Ratio	2:1
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	Not Applicable
Peel Strength (20 min, FTM1)	18 N/25mm
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Shelf Life	1 Year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Not Recommended	
Press 185°F to 210°F (85°C to 99°C)	2-6 minutes

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013