

Dry Mount Film

Dry Mount Film is a 2 mil (50 μ) plasticized clear PVC film, coated on both sides with a heat-activated solvent acrylic adhesive that is protected on both sides by a bleached Kraft gridded release paper coated on one side with siliconized PE.

- SUITABLE FOR MOUNTING TO CANVAS, HEAVILY GRAINED OR TEXTURED SUBSTRATES AND IRREGULAR SURFACES, SUCH AS MOST METALS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Release Liner	1 Side PE Coated Bleached Kraft Grid Paper (Moisture Stable)
Adhesive	Solvent Acrylic (Heat Activated)
Film	Clear PVC
Adhesive	Solvent Acrylic (Heat Activated)
Release Liner	1 Side PE Coated Bleached Kraft Grid Paper (Moisture Stable)

PRODUCT CHARACTERISTIC

Film Thickness	2 mil (50 μ)	4 mil (100 μ)
Adhesive Layer	1 mil (25 μ) on each side	
Film/Adhesive Ratio	1:2:1	
UV Protection Factor	Not Applicable	
Outdoor Durability	Not Applicable	
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)	
Shelf Life	1 Year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Not Recommended	
Press 185°F to 210°F (85°C to 99°C)	60 - 90 seconds

DRYTAC[®]
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013