

Dynamic Plus

Matte

Dynamic Plus Matte is a 3.2 mil (80 μ) monomeric soft calendared PVC laminating film with a matte finish coated on one side with a pressure sensitive acrylic adhesive that is protected by a Kraft release paper that is PE-coated on one side and siliconized on the release side.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE WHERE A NON-GLARE FINISH IS REQUIRED OR WHERE SPECIFIC LIGHTING CONDITIONS CANNOT BE CONTROLLED
- IDEAL FOR POP DISPLAYS, EXHIBITION GRAPHICS AND PROMOTIONAL SIGNAGE THAT WILL BE VIEWED UNDER DIRECT LIGHTING FROM DIFFERENT ANGLES.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80 μ) 4.2 mil
Adhesive Layer	1 mil (25 μ) (105 μ)
Film/Adhesive Ratio	3.2:1
UV Protection Factor	Film and adhesive contain UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	2 Years
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013