

Flobond™

Flobond™ is a 2 mil (50µ) carrier-free, heat reactive, pH-neutral clear mounting adhesive with an activation temperature range of 175°F - 200°F (79°C - 93°C). The bond can be re-activated by re-applying heat.

- BONDS PRINTS, POSTERS, PHOTOGRAPHS, FABRIC, PARCHMENT, OR FOILS TO A VARIETY OF SUBSTRATES, INCLUDING MAT BOARDS, FOAM BOARDS AND MOST METALS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Adhesive	2 mil (50µ) unsupported thermoplastic adhesive
-----------------	--

PRODUCT CHARACTERISTIC

Film Thickness	Not Applicable
Adhesive Layer	2 mil (50µ)
Film/Adhesive Ratio	Not Applicable
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)
Shelf Life	1 Year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com