

# Interlam™

## EcoGloss™

Interlam™ EcoGloss™ is a 1.6 mil (40µ) PP laminating film with a gloss finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with siliconized PE. Interlam™ EcoGloss™ is phthalate-free and provides excellent image enhancement and moisture protection for indoor graphics. It has been internationally approved for direct food contact.

- IDEAL FOR POP DISPLAYS, INDOOR AND SHORT-TERM OUTDOOR SIGNAGE, ARCHITECTURAL RENDERINGS, MAPS, AND OTHER INDOOR PROMOTIONAL GRAPHICS USED UNDER DIRECT LIGHT
- SUITABLE FOR FOOD PACKAGING, FOOD SHELVES AND OTHER APPLICATIONS WITH DIRECT FOOD CONTACT
- NOT RECOMMENDED FOR LAMINATING VINYL BANNERS OR OTHER APPLICATIONS WHERE THE LAMINATE WILL BE REQUIRED TO EXPAND AND CONTRACT WITH THE PRINT MEDIA.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Gloss Clear PP
<b>Adhesive</b>	Aqueous Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconized 1 Side PE Coated Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	1.6 mil (40µ)   2.6 mil
<b>Adhesive Layer</b>	1 mil (25µ)   (65µ)
<b>Film/Adhesive Ratio</b>	1.6:1
<b>UV Protection Factor</b>	Not Applicable
<b>Outdoor Durability</b>	Not Applicable
<b>Service Temperature Range</b>	-13°F to 302°F (-25°C to 150°C)
<b>Peel Strength (20 min, FTM1)</b>	11 N/25mm
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013