

# Interlam™

## EcoTex™

Interlam™ EcoTex™ is a 5.6 mil (140µ) PP laminating film with a pebble textured finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with siliconised PE. Interlam™ EcoTex™ is phthalate-free and provides excellent image enhancement and moisture protection for indoor graphics.

- THE SCUFF-RESISTANT, PEBBLE TEXTURED FINISH MAKES THIS LAMINATING FILM SUITABLE FOR GRAPHICS WHERE EXTENSIVE HANDLING MAY BE INVOLVED
- IDEAL FOR LAMINATING AND ENCAPSULATING TRADESHOW AND BANNER STAND GRAPHICS, SIGNAGE IN HIGH TRAFFIC AREAS, COUNTER MATS, PLACEMATS, AND OTHER GRAPHICS WHERE A SCUFF-RESISTANT FINISH IS REQUIRED AND COST IS A KEY FACTOR
- IDEAL FOR SINGLE-SIDED LAMINATION DUE TO ITS DIMENSIONAL STABILITY
- OFFERS EXCELLENT UV PROTECTION FOR HIGH QUALITY IMAGES, PHOTOGRAPHIC PRINTS, WALLCOVERINGS, AND SELF-ADHESIVE VINYL

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Pebble Textured PP
<b>Adhesive</b>	Aqueous Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconised 1 Side PE Coated Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	5.6 mil (140µ)   6.6 mil
<b>Adhesive Layer</b>	1 mil (25µ)   (165µ)
<b>Film/Adhesive Ratio</b>	5.6:1
<b>UV Protection Factor</b>	Adhesive contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image
<b>Outdoor Durability</b>	Not Applicable
<b>Service Temperature Range</b>	-4°F to 248°F (-20°C to 120°C)
<b>Peel Strength (20 min, FTM1)</b>	11 N/25mm
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
bristol@drytac.com  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
toronto@drytac.com  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013