

## Pro Emerytex®

Interlam™ Pro Emerytex® is a 4 mil (100µ) monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side. Interlam™ Pro Emerytex® has been tested according to the EN 13036-4 test method and awarded a rating of low slip potential.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN HIGH TRAFFIC INDOOR AND OUTDOOR DISPLAY AREAS
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A SCUFF-RESISTANT FINISH IS REQUIRED
- CAN BE COMBINED WITH DRYTAC'S PRINT MEDIA TO CREATE A SLIP-RESISTANT FLOOR GRAPHICS.
- FILM AND ADHESIVE CONTAIN UV STABILIZERS, WHICH PREVENT FILM DEGRADATION AND PROVIDE UV PROTECTION TO THE UNDERLYING IMAGE

### PROCESS SETTINGS

Equipment Type & Temperature      Speed

**Roller Laminator**  
Room temperature  
to 104°F (40°C)

1 ft to 8 ft (0.3m to  
2.5m) per minute

Press

Not recommended

**For more information,  
performance and warranty  
guidelines please contact your  
local Drytac office.**

© 2020 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

|                      |   |
|----------------------|---|
| <b>Film</b>          | Matte Pebble Textured Monomeric Soft Calendared PVC |
| <b>Adhesive</b>      | Acrylic (Pressure Sensitive)                        |
| <b>Release Liner</b> | 2 Side PE Coated, 1 Side Siliconised Kraft          |

### PRODUCT CHARACTERISTICS

|                                     |  |
|-------------------------------------|--|
| <b>Film Thickness</b>               | 4 mil (100µ)   5 mil   |
| <b>Adhesive Layer</b>               | 1 mil (25µ)   (125µ)   |
| <b>Outdoor Durability</b>           | 5 Years (Ink Dependent)  |
| <b>Fire Ratings</b>                 | Class 0 (BS 476 Part 6 and 7)<br>Class 1 or A (ASTM E-84)<br>PASS (CAN/ULC-S102)   |
| <b>Paired Solution Fire Rating</b>  | B <sub>fl</sub> - s1 (EN 13501-1)<br>when paired with Polar Grip print media   |
| <b>FDA Certification</b>            | PASS (FDA 21 CFR 177.1975)   |
| <b>Slip Certifications</b>          | R 11 (DIN 51130:2010)<br>Dry: 62; Wet: 35 (HB198:2014 (AS/NZS 4586))<br>Acceptable (ANSI B101.3)<br>Low Slip Potential; Dry: 64 Wet: 36 (EN 13036-4) |
| <b>Application Temperature</b>      | >41°F (20°C)   |
| <b>Service Temperature Range</b>    | -4°F to 203°F (-20°C to 95°C)  |
| <b>Peel Strength (20 min, FTM1)</b> | 11 N/25mm  |
| <b>Shelf Life</b>                   | 2 Years  |
| <b>Storage Conditions</b>           | 59°F to 72°F (15°C to 22°C);<br>50 - 55% Relative Humidity   |

# DRYTAC®

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013