

## Pro Glossy

Interlam™ Pro Glossy is a 3 mil (75µ) monomeric soft calendared PVC laminating film with a glossy finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE ON FLEXIBLE MEDIA SUBSTRATES WHERE A GLOSS FINISH IS REQUIRED

- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, EVENT SIGNAGE AND PHOTOGRAPHIC IMAGES

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Gloss Monomeric Soft Calendared PVC
<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Side PE Coated, 1 Side Siliconized Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	3 mil (75µ)   4 mil
<b>Adhesive Layer</b>	1 mil (25µ)   (100µ)
<b>Film/Adhesive Ratio</b>	3:1
<b>UV Protection Factor</b>	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
<b>Outdoor Durability</b>	3 Years
<b>Application Temperature</b>	>41°F (20°C)
<b>Service Temperature Range</b>	-13°F to 302°F (-25°C to 150°C)
<b>Peel Strength (20 min, FTM1)</b>	11 N/25mm
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

# DRYTAC®

## ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013