

Pro Lustre

Interlam™ Pro Lustre is a 3 mil (75µ) monomeric soft calendared PVC laminating film with a lustre finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side.

- LOW SHEEN WITHOUT LOSS OF CONTRAST OR SHARPNESS MAKES INTERLAM™ PRO LUSTRE EFFECTIVE FOR A WIDE RANGE OF APPLICATIONS
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, AND EVENT SIGNAGE

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Lustre Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 1 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3 mil (75µ) 4 mil
Adhesive Layer	1 mil (25µ) (100µ)
Film/Adhesive Ratio	3:1
UV Protection Factor	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	3 Years
Application Temperature	>41°F (20°C)
Service Temperature Range	-13°F to 302°F (-25°C to 150°C)
Peel Strength (20 min, FTM1)	11 N/25mm
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013