

# Interlam™

## Pro Matte

Interlam™ Pro Matte is a 75µ (3 mil) monomeric soft calendared PVC laminating film with a matte finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with PE and siliconised on the release side.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE WHERE A NON-GLARE FINISH IS REQUIRED OR WHERE SPECIFIC LIGHTING CONDITIONS CANNOT BE CONTROLLED
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, EVENT SIGNAGE AND PHOTOGRAPHIC IMAGES
- INTERLAM™ PRO MATTE HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Matte Monomeric Soft Calendared PVC
<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Release Liner</b>	1 Side PE Coated

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	3 mil (75µ)   4 mil
<b>Adhesive Layer</b>	1 mil (25µ)   (100µ)
<b>UV Protection Factor</b>	Film contains UV stabilizers, which prevent film degradation and provide UV protection to the underlying image
<b>Outdoor Durability</b>	3 Years (Ink Dependent)
<b>Fire Rating</b>	Class 0
<b>Application Temperature</b>	>41°F (20°C)
<b>Service Temperature Range</b>	-13°F to 302°F (-25°C to 150°C)
<b>Peel Strength (20 min, FTM1)</b>	11 N/25mm
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

# DRYTAC®

## ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013