

Multi-Heat Adhesive

MHA™ (Multi-Heat Adhesive) is a heat activated, solvent acrylic mounting adhesive that is protected by a moisture stable bleached Kraft differential release paper coated on both sides with siliconized PE. This carrier-free adhesive offers a superior bond to flexible and rollable substrates, such as Expanded PVC (e.g. Sintra™), and is an excellent solution when paired with Drytac's MediaShield™ and MHL™ laminates. It has a low initial tack before heat is applied that allows it to be re-positioned, and it can be heated multiple times to activate the adhesive. After activation is complete, a strong bond is formed. MHA™ can be die cut and is considered self-trimming since it is carrier-free.

- RECOMMENDED FOR MOUNTING OF CANVAS, WHERE THE BACK OF THE CANVAS AND THE SUBSTRATE TO BE USED ARE BOTH COATED WITH MHA™ AND MARRIED TOGETHER FOR A VERY STRONG BOND
- IDEAL FOR MOUNTING IMAGES ON MDF TO CREATE PLAQUES; CAN BE TRIMMED AND FOILED WITHOUT THE IMAGES LIFTING
- SUITABLE FOR MANUFACTURING PROCESSES TO CREATE A STRONG BOND BETWEEN TWO SUBSTRATES

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Adhesive	Solvent Acrylic (Heat Activated)
Release Liner	2 Side PE Coated Bleached Kraft Differential Release Paper (Moisture Stable)

PRODUCT CHARACTERISTIC

Film Thickness	Not Applicable (no carrier) 1 mil (25µ)
Adhesive Layer	1 mil (25µ)
Film/Adhesive Ratio	1:1:1
UV Protection Factor	Not Applicable
Outdoor Durability	6 months will only show inconsequential changes in properties of the product
Service Temperature Range	-4°F to 175°F (-20°C to 79°C)
Shelf Life	1 Year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator 185°F to 220°F (85°C to 104°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press 195°F (91°C)	Dwell Time: 3 minutes

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013