

## Low Temperature Frost

MHL™ Frost™ is a 6 mil (152µ) embossed composite thermal laminating film with a crystal textured finish that offers a scratch-resistant, non-reflective surface for graphic enhancement. The finish minimizes reflectivity of bright light surroundings while allowing brilliant colors to shine through. MHL™ Frost™ incorporates ultra low melt-point technology in a textured laminating film. The film is resistant to water, oil, acid, alkali, and fingerprints. It is very durable and can be die-cut.

- RECOMMENDED FOR DISPLAY APPLICATIONS, ESPECIALLY EXHIBITION AND POS GRAPHICS
- IDEAL FOR POP-UP DISPLAY PANELS AND ROLL-UP BANNERS
- PERFORMS WELL IN HIGH-TRAFFIC AREAS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT CHARACTERISTIC

Film Thickness	6 mil (152µ)
Film/Adhesive Ratio	3:3
Processing Temperature	185°F to 195°F (85°C to 91°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

**DRYTAC**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013