

MHL™

Scribe™

MHL™ Scribe™ is a 3 mil (75µ) high clarity, abrasion-resistant PP thermal laminating film with a gloss finish. The film is engineered with a specially formulated copolymer thermal adhesive for a low melt-point for single-sided lamination. With its dry erase characteristics, dry erase markers can be wiped clean with a dry cloth.

- IDEAL FOR LAMINATING BOOK JACKETS, REPORT COVERS AND OTHER SPECIALTY APPLICATIONS
- SUITABLE FOR COURTROOM DISPLAYS
- CAN BE USED FOR SHORT-TERM DRY ERASE BOARDS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT CHARACTERISTIC

Film Thickness	3 mil (75µ)
Film/Adhesive Ratio	0.5:2.5
Processing Temperature	210°F to 230°F (99°C to 110°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com