

Soft Velvet Touch

MHL™ Soft Velvet Touch is a 1.4 mil (35µ) nylon thermal laminating film with a velvet matte finish and anti-curl properties. It provides excellent clarity and a soft, luxurious feel to graphics. The film also offers scuff resistance for added protection.

- RECOMMENDED FOR SOFT BOOK COVERS, POSTCARDS, POCKET FOLDERS, BROCHURES, CALENDARS, AND PRESENTATION COVERS
- IDEAL FOR SINGLE-SIDED LAMINATION

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT CHARACTERISTIC

Film Thickness	1.4 mil (35µ)
Film/Adhesive Ratio	0.7:0.7
Processing Temperature	240°F to 260°F (115°C to 127°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013