

MHL™ Standard Temperature Gloss is a 1.7 mil (43µ) high clarity, abrasion-resistant PET thermal laminating film designed for high-speed single- or double-sided lamination. The film is resistant to water, oil, acid, and alkali and can be die cut.

- IDEAL FOR LAMINATING BOOK JACKETS, POSTERS, MENUS, AND MAPS
- RECOMMENDED FOR APPLICATIONS THAT REQUIRE EXCELLENT CLARITY AND PROTECTION

PRODUCT CHARACTERISTIC

Film Thickness	11.7 mil (43µ)
Film/Adhesive Ratio	0.5:1.2
Processing Temperature	210°F to 230°F (99°C to 110°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

DRYTAC®
ADHESIVE SCIENCE