MultiTac™

TECHNICAL SPECIFICATION

MultiTac™ is a high quality PET film, coated on both sides with a pressure sensitive, high tack acrylic adhesive, one of which is protected by fine paper coated on both sides with siliconized PE. The adhesive is self-wound on the release liner. A clear and white version are available.

- SUITABLE FOR IMAGE DECAL AND HIGH-VOLUME MOUNTING OF GRAPHICS ONTO DIFFICULT SUBSTRATES, SUCH AS FOREX™, MDF, GATORBOARD™, ULTRABOARD™, FOAMEX™, OR SINTRA™
- THE WHITE VERSION OF MULTITAC™ OFFERS EXCELLENT OPACITY AND THE ABILITY TO MOUNT TO DARK SUBSTRATES

PRODUCT STRUCTURE

Adhesive	Acrylic (Pressure Sensitive)
Film	Clear PET or White PET
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 2 Side Siliconized Fine Paper

PRODUCT CHARACTERISTIC

Adhesive Layer	1.2 mil (30µ) on each side
Adhesive pH	6.0
180° Peel (ozf/in)	67
Service Temperature Range	-31˚F to 158˚F (-35˚C to 70˚C)
Shelf Life	1 year
Storage Conditions	59˚F to 72˚F (15˚C to 22˚C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & **Temperature**	**Speed**
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

DRYTAC®
ADHESIVE SCIENCE

Europe
Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada
30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA
5401 B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013