

Removable

OptiTac is a 1.5 mil (38μ) high quality, optically clear PET film, coated on one side with a pressure sensitive, permanent solvent acrylic adhesive and the other side with a pressure sensitive, removable solvent acrylic adhesive both of which are protected by a clear PET release liner. OptiTac is made using the finest optical clarity components. It offers excellent UV stability to graphic prints.

- RECOMMENDED FOR SECOND SURFACE MOUNTING (COMMONLY REFERRED TO AS FACE MOUNTING) OF IMAGES TO CLEAR SUBSTRATES, SUCH AS PETG™, PLEXIGLAS™, ACRYLIC, POLYCARBONATE, AND GLASS
- IDEAL FOR LENTICULAR IMAGING APPLICATIONS, BACKLIT DISPLAY TRANSPARENCIES, TOUCH SCREEN DISPLAYS, AND HIGH QUALITY PHOTOGRAPHIC AND INKJET PRINTED IMAGES
- SUITABLE FOR WINDOW GRAPHICS AND TEMPORARY SIGNAGE
- INDOOR AND SHORT-TERM OUTDOOR USE
- WITH REMOVABLE ADHESIVE ON ONE SIDE, OPTITAC REMOVABLE ALLOWS THE REUSE OF EXPENSIVE SUBSTRATES SUCH AS PLEXIGLAS™

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Release Liner	Siliconized 1 Side PET
Adhesive	Permanent Solvent Acrylic (Pressure Sensitive)
Film	Clear PET
Adhesive	Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	Siliconized 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	1.5 mil (38μ)	3.5 mil (88μ)
Adhesive Layer	1 mil (25μ) on each side	
Film/Adhesive Ratio	1:1.5:1	
UV Protection Factor	UV Stable	
Outdoor Durability	1 Year	
Peel Strength (20 min, FTM1)	15.2 N/25mm (glass 24 hours)	
Service Temperature Range	-40°F to 212°F (-40°C to 100°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013