

# Protac™

## Canvastex™

Protac™ Canvastex™ is a 4 mil (100µ) monomeric calendared PVC laminating film with an embossed canvas finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a one side siliconized PET release liner. Both the film and adhesive contain UV stabilizers, which protect against UV degradation.

- IDEAL FOR PORTRAIT PHOTOGRAPHY, BOOK AND ALBUM COVERS, FRAMED MATS, DIPLOMAS, AND CERTIFICATES
- CAN BE USED ON POSTERS TO SIMULATE THE LOOK OF AN ORIGINAL OIL PAINTING

PROTAC™ CANVASTEX™ HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Canvas Textured Monomeric Calendared PVC
<b>Adhesive</b>	Solvent Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconized 1 Side PET

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	4 mil (100µ)	5 mil (125µ)
<b>Adhesive Layer</b>	1 mil (25µ)	
<b>Film/Adhesive Ratio</b>	4:1	
<b>UV Protection Factor</b>	Film contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image	
<b>Outdoor Durability</b>	3 Years	
<b>Peel Strength (20 min, FTM1)</b>	12 N/25mm	
<b>Service Temperature Range</b>	-4°F to 230°F (-20°C to 110°C)	
<b>Shelf Life</b>	1 year	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
bristol@drytac.com  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
toronto@drytac.com  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013