

Protac™

Deep Textured Canvastex™

Protac™ Deep Textured Canvastex™ is a 7.5 mil (190µ) embossed monomeric calendared PVC laminating film with a deep canvas textured finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side. Both the film and adhesive contain UV stabilizers, which protect against UV degradation.

- CAN BE USED AS AN ALTERNATIVE TO MOUNTING OR PRINTING ONTO CANVAS
- CREATES THE ILLUSION THAT AN IMAGE HAS BEEN PRINTED ON COARSE CANVAS
- PROTAC™ DEEP TEXTURED CANVASTEX™ HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Deep Canvas Textured Monomeric Calendared PVC
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 1 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	7.5 mil (190µ)	8.5 mil (215µ)
Adhesive Layer	1 mil (25µ)	
Film/Adhesive Ratio	7.5:1	
UV Protection Factor	Film contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image	
Outdoor Durability	3 Years	
Peel Strength (20 min, FTM1)	15 N/25mm	
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013