

High Gloss

Protac™ High Gloss is a 4 mil (100µ) clear PET laminating film with a high gloss finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a one side siliconized PET release liner.

- ADDS DEPTH AND DETAIL TO ANY IMAGE, WHETHER IT IS PHOTOGRAPHIC, INKJET OR OTHER OUTPUT MEDIA
- IDEAL FOR PHOTOGRAPHIC PRINTS, PHOTO ALBUMS, POP DISPLAYS, OR ANYWHERE A HIGH GLOSS FINISH IS DESIRED

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	High Gloss PET
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	Siliconized 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ) 5 mil
Adhesive Layer	1 mil (25µ) (125µ)
Film/Adhesive Ratio	4:1
UV Protection Factor	Not Applicable
Outdoor Durability	1 Year
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Peel Strength (20 min, FTM1)	14.7 N/25mm
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013