

Protac™

Leather

Protac™ Leather is a 150µ (6 mil) monomeric calendared PVC laminating film with a leather finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a one side siliconised polyester release liner. Both the film and the adhesive contain UV stabilisers, which protect against both UV degradation and potential mechanical damage. Available in various sizes.

- ITS LOW SHEEN WITHOUT LOSS OF CONTRAST OR SHARPNESS MAKES PROTAC™ LEATHER EFFECTIVE FOR A WIDE RANGE OF APPLICATIONS
- IDEAL FOR ADDING A LEATHER TEXTURED FINISH TO BOOKS AND ALBUMS OR FOR COVERING MOUNT BOARDS TO CREATE LEATHER MOUNTS
- RECOMMENDED FOR PHOTOGRAPHIC QUALITY IMAGES THAT WILL BE VIEWED UNDER DIRECT LIGHTING CONDITIONS IN INDOOR AND OUTDOOR APPLICATIONS
- PROTAC™ LEATHER HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Leather Textured Monomeric Calendared PVC
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	1 Side Siliconised Polyester

PRODUCT CHARACTERISTIC

Film Thickness	6 mil (150µ) 6.9 mil
Adhesive Layer	0.9 mil (24µ) (174µ)
Film/Adhesive Ratio	6:0.9
UV Protection Factor	Film contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	3+ Years
Peel Strength (20 min, FTM1)	12 N/25mm
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com