

Polycarbonate

Protac™ Polycarbonate is a clear polycarbonate laminating film with a velvet matte pebble textured finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a PET film with a single-side easy release coating. A 10 mil (250µ) and 15 mil (375µ) version are available.

- IDEAL FOR POP-UP BOOTHS AND EXHIBITION BACK WALLS
- THE SCRATCH-RESISTANT SURFACE ENSURES LONG LASTING PROTECTION

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Velvet Matte Pebble Textured Polycarbonate
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	PET (Moisture Stable)

PRODUCT CHARACTERISTIC

Film Thickness	10/15 mil (250/375µ) 12/17 mil (300/425µ)
Adhesive Layer	2 mil (50µ)
Film/Adhesive Ratio	10:2/15:2
UV Protection Factor	Not Applicable
Outdoor Durability	3 months will only show inconsequential changes in properties of this product
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)
Peel Strength (20 min, FTM1)	12 N/25mm
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 105°F (40°C)	1 ft to 4 ft (0.3m to 1.25m) per minute
Press	Not recommended

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013