

# Protac™

## ScuffGuard

Protac™ Scuff Guard is a 6 mil (150µ) monomeric calendared PVC protective laminating film with a scuff-resistant, textured matte finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a single-sided, siliconised Kraft release liner. The anti-slip properties of Protac™ Scuff Guard have been tested in accordance with DIN 51130 standards and have been awarded an R10 rating.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN MEDIUM TO HIGH-TRAFFIC INDOOR DISPLAY AREAS

PROVIDES UV PROTECTION

- FOR INDOOR AND OUTDOOR GRAPHICS (UP TO 3 YEARS)

- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A SCUFF-RESISTANT FINISH IS REQUIRED

- CAN BE COMBINED WITH DRYTAC'S FLOORTAC™ PRINT MEDIA TO CREATE A SLIP-RESISTANT FLOOR GRAPHIC

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Matte Textured Monomeric Calendared PVC
<b>Adhesive</b>	Solvent Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconised 1 Side White Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	6 mil (150µ)   6.8 mil
<b>Adhesive Layer</b>	0.8 mil (20µ)   (170µ)
<b>Film/Adhesive Ratio</b>	6:0.8
<b>UV Protection Factor</b>	Film contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image
<b>Outdoor Durability</b>	3 Years
<b>Service Temperature Range</b>	-4°F to 230°F (-20°C to 110°C)
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
bristol@drytac.com  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
toronto@drytac.com  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013