

Protac™

Sheentex™

Protac™ Sheentex™ is a 4 mil (100µ) monomeric calendared PVC laminating film with a satin pebble finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconised on the release side. Both the film and adhesive contain UV stabilisers, which protect against UV degradation.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN HIGH-TRAFFIC INDOOR DISPLAY AREAS
- IDEAL FOR LAMINATING PLACEMATS, COUNTER MATS AND OTHER SIMILAR APPLICATIONS

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Satin Pebble Monomeric Calendared PVC
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 1 Side Siliconised Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ)	5 mil (125µ)
Adhesive Layer	1 mil (25µ)	
Film/Adhesive Ratio	4:1	
UV Protection Factor	Film contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image	
Outdoor Durability	3 Years	
Peel Strength (20 min, FTM1)	12 N/25mm	
Service Temperature Range	-4°F to 230°F (-20°C to 110°C)	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013