

ReTac®

Duo

ReTac® Duo is a 1 mil (25µ) clear PET film, coated on both sides with adhesive. It has a permanent adhesive on one side to be used on graphic prints and ReTac® ultra removable adhesive on the other, allowing it to be easily removed and re-positioned for repeated use. ReTac® Duo is designed to adhere to walls, doors or any smooth surface without leaving behind residue or damaging the surface when removed. The adhesive is self-wound on a two-sided, PE coated siliconized Kraft release paper.

- IDEAL FOR TRANSFORMING PHOTOS, POSTERS, GRAPHICS, OR NEWS CLIPPINGS INTO WALL GRAPHICS OR RE-POSITIONABLE DECALS

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Adhesive	Permanent Acrylic (Pressure Sensitive)
Film	Clear PET
Adhesive	ReTac® ultra removable and re-positionable adhesive
Release Liner	2 Side PE Coated, 2 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	1 mil (25µ)	3 mil (75µ)
Adhesive Layer	1 mil (25µ) on each side	
Film/Adhesive Ratio	1:1:1	
UV Protection Factor	Not Applicable	
Outdoor Durability	Not Applicable	
Service Temperature Range	-22°F to 284°F (-30°C to 140°C)	
Shelf Life	1 Year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013