

# ReTac®

## Duo

ReTac® Duo is a 0.5 mil (12.5µ) clear PET film, coated on both sides with adhesive. It has a permanent adhesive on one side to be used on graphic prints and ReTac® ultra removable adhesive on the other, allowing it to be easily removed and re-positioned for repeated use. ReTac® Duo is designed to adhere to walls, doors or any smooth surface without leaving behind residue or damaging the surface when removed. The adhesive is self-wound on a two-sided, PE coated siliconized Kraft release paper.

- IDEAL FOR TRANSFORMING PHOTOS, POSTERS, GRAPHICS, OR NEWS CLIPPINGS INTO WALL OR WINDOW GRAPHICS OR RE-POSITIONABLE DECALS

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2023 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Adhesive</b>	Permanent Acrylic (Pressure Sensitive)
<b>Film</b>	Clear PET
<b>Adhesive</b>	ReTac® ultra removable and re-positionable adhesive
<b>Release Liner</b>	2 Side PE Coated, 2 Side Siliconized Kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	0.5 mil (12.5µ)   1.5 mil
<b>Adhesive Layer</b>	1 mil (25µ) on each side   (37.5µ)
<b>Outdoor Durability</b>	2 Years (when applied to smooth glass surfaces)
<b>Application Temperature</b>	41°F (5°C)
<b>Service Temperature Range</b>	40°F to 120°F (4.4°C to 48.9°C)
<b>Outdoor Service Temperature Range</b> (when applied to smooth glass surfaces)*	-4°F to 120°F (-20°C to 48.9°C)
<b>Shelf Life</b>	1 Year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

\* Interior glass recommended.

# DRYTAC®

## ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401 B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)