

RemoTac™ is a 0.5 mil (12µ) clear PET film, coated on one side with a pressure sensitive, removable acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with siliconized PE. The other side of the film is coated with a pressure sensitive, permanent acrylic adhesive. The adhesive is self-wound on the release liner.

- IDEAL FOR INTERCHANGEABLE SIGNS AND GRAPHICS FOR COUNTERTOPS, PRESENTATION GRAPHICS AND RETAIL DISPLAY BOARDS
- EASILY REMOVES FROM A VARIETY OF SUBSTRATES, INCLUDING GLASS, PAINTED METAL AND ALUMINIUM
- RECOMMENDED FOR DIFFICULT, LOW ENERGY SURFACES DUE TO ITS HIGH TACK
- SUITABLE FOR BOTH INDOOR AND SHORT-TERM OUTDOOR USE

### PRODUCT STRUCTURE

Release Liner	Permanent Acrylic (Pressure Sensitive)
Film	Clear PET
Adhesive	Removable Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated, 2 Side Siliconized Kraft

### PRODUCT CHARACTERISTIC

Film Thickness	0.5 mil (12µ)	2.5 mil (62µ)
Adhesive Layer	1 mil (25µ) on each side	
Film/Adhesive Ratio	1:0.5:1	
UV Protection Factor	UV Stable	
Outdoor Durability	3 Months	
Peel Strength (20 min, FTM1)	12 N/25mm (permanent) 7.5 N/25mm (removable)	
Service Temperature Range	-22°F to 284°F (-30°C to 140°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

# DRYTAC®

## ADHESIVE SCIENCE

For more information,  
performance and warranty  
guidelines please contact your  
local Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
bristol@drytac.com  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
toronto@drytac.com  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013