

## White

SureTac™ White is a 1.4 mil (36µ) white PP film coated on both sides with a pressure sensitive, high shear, acid-free solvent acrylic adhesive that is protected by a moisture stable bleached Kraft differential release paper coated on both sides with siliconized PE. The adhesive is self-wound on the release liner.

- COMPATIBLE WITH A WIDE VARIETY OF MEDIA AND SUBSTRATES
- ITS SOLVENT ACRYLIC ADHESIVE OFFERS A STABLE AND PERMANENT BOND FOR OUTDOOR USE
- WHITE CARRIER BLOCKS SHOW-THROUGH ON DARK SUBSTRATES.
- UV RESISTANT
- HAS A HIGH BOND STRENGTH TO MEDIA AND SUBSTRATES SUCH AS POLYESTER AND POLYCARBONATE.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Adhesive</b>	Solvent Acrylic (Pressure Sensitive)
<b>Carrier</b>	White PP
<b>Adhesive</b>	Solvent Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Side PE Coated Bleached Kraft Differential Release Paper

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	1.4 mil (36µ)	3.6 mil (92µ)
<b>Adhesive Layer</b>	1.1 mil (28µ) on each side	
<b>Film/Adhesive Ratio</b>	1.1:1.4:1.1	
<b>UV Protection Factor</b>	1 year	
<b>Outdoor Durability</b>	UV Resistant	
<b>Service Temperature Range</b>	-30°F to 220°F (-34°C to 104°C)	
<b>Shelf Life</b>	2 Years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 100°F (38°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013