

White

SureTac™ White is a 1.4 mil (36µ) white PP film coated on both sides with a pressure sensitive, high shear, acid-free solvent acrylic adhesive that is protected by a moisture stable bleached Kraft differential release paper coated on both sides with siliconized PE. The adhesive is self-wound on the release liner.

- COMPATIBLE WITH A WIDE VARIETY OF MEDIA AND SUBSTRATES
- ITS SOLVENT ACRYLIC ADHESIVE OFFERS A STABLE AND PERMANENT BOND FOR OUTDOOR USE
- WHITE CARRIER BLOCKS SHOW-THROUGH ON DARK SUBSTRATES.
- UV RESISTANT
- HAS A HIGH BOND STRENGTH TO MEDIA AND SUBSTRATES SUCH AS POLYESTER AND POLYCARBONATE.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

| | |
|---------------|--|
| Adhesive | Solvent Acrylic (Pressure Sensitive) |
| Carrier | White PP |
| Adhesive | Solvent Acrylic (Pressure Sensitive) |
| Release Liner | 2 Side PE Coated Bleached Kraft Differential Release Paper |

PRODUCT CHARACTERISTIC

| | | |
|---------------------------|---|---------------|
| Film Thickness | 1.4 mil (36µ) | 3.6 mil (92µ) |
| Adhesive Layer | 1.1 mil (28µ) on each side | |
| Film/Adhesive Ratio | 1.1:1.4:1.1 | |
| UV Protection Factor | 1 year | |
| Outdoor Durability | UV Resistant | |
| Service Temperature Range | -30°F to 220°F (-34°C to 104°C) | |
| Shelf Life | 1 Year | |
| Storage Conditions | 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity | |

PROCESS SETTINGS

| Equipment Type & Temperature | Speed |
|--|--|
| Roller Laminator Room temperature to 100°F (38°C) | 1 ft to 8 ft (0.3m to 2.5m) per minute |
| Press | Not recommended |

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013