

Trimount™ is a 2.6 mil (65µ) pH-neutral white mounting tissue, coated on both sides with a heat-activated solvent acrylic adhesive that is tack-free at normal ambient temperature and does not require a release liner.

- FOR USE IN ALL TYPES OF DRY MOUNTING PRESSES
- RECOMMENDED FOR BONDING RESIN-COATED PHOTOGRAPHIC PAPER AND PRINTED MATERIALS TO SMOOTH SURFACES

### PRODUCT STRUCTURE

<b>Adhesive</b>	Solvent Acrylic (Heat Activated)
<b>Film</b>	Off White Kraft Paper
<b>Adhesive</b>	Solvent Acrylic (Heat Activated)

### PRODUCT CHARACTERISTIC

<b>Paper Weight</b>	50 gsm	3.6 mil (89µ)
<b>Adhesive Layer</b>	0.5 mil (12µ) on each side	
<b>Film/Adhesive Ratio</b>	0.5:2.6:0.5	
<b>UV Protection Factor</b>	Not Applicable	
<b>Outdoor Durability</b>	Not Applicable	
<b>Service Temperature Range</b>	-4°F to 203°F (-20°C to 95°C)	
<b>Shelf Life</b>	2 Years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Not Recommended	Not Recommended
<b>Press</b> 194°F to 210°F (90°C to 99°C)	60 - 90 seconds

# DRYTAC®

## ADHESIVE SCIENCE

For more information,  
performance and warranty guide  
lines please contact your local  
Drytac office.

© 2022 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401 B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013