

DRYTAC®

JM18, JM26 & JM34

These smaller JetMounter™ models are motorized table-top laminators operated by a foot switch, leaving both hands free to handle the work being processed. The JM18, JM26 and JM34 are designed for mounting and laminating inkjet output, but are equally capable of handling photographic or any printed media. All models include a supply shaft and photo cell safety protection.



Note: *There are no rewind shafts on these models.*

JM18, JM26 & JM34 SPECIFICATIONS

	JM18	JM26	JM34
Max Laminating Width	18.25" (464 mm)	26.25" (667 mm)	34" (863 mm)
Max Board Thickness	1" (25 mm)	1" (25 mm)	1" (25 mm)
Unpacked Weight	51 lbs (23 kg)	53 lbs (24 kg)	70.5 lbs (32 kg)
Width	25.5" (650 mm)	33.25" (845 mm)	41" (1050 mm)
Depth	11.75" (300 mm)	12" (310 mm)	11.8" (300 mm)
Height	13" (330 mm)	12" (310 mm)	13.38" (340 mm)
Roller Diameter	2.5" (63 mm)	2.5" (63 mm)	2.5" (63 mm)
Speed Range	2.5 - 18 fpm (0.76 - 5.5 mpm)	2.5 - 18 fpm (0.76 - 5.5 mpm)	2.5 - 18 fpm (0.76 - 5.5 mpm)
Power	110V, 50/60Hz	110V, 50/60Hz	110V, 50/60Hz

ML25

This table-top manual laminator is an inexpensive option for small photo studios or copy shops that want to quickly mount or laminate small pieces. Simple, durable construction makes this model easy to use. It also folds up for easy storage and transport.

ML25 SPECIFICATIONS

Max Laminating Width	25.5" (648 mm)
Max Nip Opening	1" (25 mm)
Weight	31 lbs (14 kg)
Width	27.375" (695 mm)
Depth	24.5" (622 mm)
Height	10.25" (260 mm)
Roller Diameter	2.5" (63 mm)



Drytac Corporation
5601 Eastport Boulevard
Richmond, VA 23231
United States
customerservice@drytac.com
+1-800-280-6013

Drytac Canada Inc.
105 Nuggett Court
Brampton, Ontario L6T 5A9
Canada
toronto@drytac.com
+1-800-353-2883

Drytac Europe Ltd.
Filwood Road
Fishponds, Bristol BS16 3RY
United Kingdom
bristol@drytac.com
+44 (0) 117-958-6500