

Protac™

Anti-Scratch Gloss

Protac™ Anti-Scratch Gloss is a 4 mil (100µ) or 10 mil (250µ) clear PET laminating film with a scratch-resistant hard coat, high gloss finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a PET release liner. The scratch-resistant hard coat adds protection for a sharper finish.

- ADDS DEPTH AND DETAIL TO ANY IMAGE, WHETHER IT IS PHOTOGRAPHIC, INKJET OR OTHER OUTPUT MEDIA
- THE SCRATCH-RESISTANT HARD COAT ADDS PROTECTION FOR A SHARPER FINISH
- IDEAL FOR PHOTOGRAPHS, INKJET PRINTS, DEPARTMENT STORE ADVERTISING, POP DISPLAYS, OR ANYWHERE A HIGH-GLOSS, ALMOST MIRROR-LIKE FINISH IS DESIRED

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	High Gloss Clear PET with Scratch-Resistant Hard Coat
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	PET (Moisture Stable)

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ) or 10 (250µ)
Adhesive Layer	1 mil (25µ)
UV Protection Factor	Yes
Outdoor Durability	5 Years
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Application Temperature	>41°F (5°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator 120°F (49°C)	1 ft to 6 ft (0.3m to 1.75m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com