

# Protac™

## Scribe™

Protac™ Scribe™ is a 2 mil (50µ) biaxially-oriented PP laminating film with a gloss finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with a siliconized PE.

- SUITABLE FOR APPLICATION TO HEAT SENSITIVE OUTPUT AND HIGH INK COVERAGE IMAGES PRINTED ON PHOTO GLOSS PAPER
- IDEAL FOR DRY ERASE PRESENTATION BOARDS, SCHEDULES, YEARLY PLANNERS, OR MAPS.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Gloss Clear PP
<b>Adhesive</b>	Aqueous Acrylic (Pressure Sensitive)
<b>Release Liner</b>	Siliconized 1 Side PE Coated Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	2 mil (50µ)   3 mil
<b>Adhesive Layer</b>	1 mil (25µ)   (75µ)
<b>Film/Adhesive Ratio</b>	2:1
<b>UV Protection</b>	Yes
<b>Outdoor Durability</b>	Not Applicable
<b>Service Temperature Range</b>	-4°F to 230°F (-20°C to 110°C)
<b>Peel Strength (20 min, FTM1)</b>	11 N/25mm
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)