

Protac™

ScuffGuard

Protac™ ScuffGuard is a 6 mil (150µ) monomeric calendared PVC protective laminating film with a scuff-resistant, textured matte finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a single-sided, siliconised Kraft release liner.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN MEDIUM TO HIGH-TRAFFIC INDOOR DISPLAY AREAS
- PROVIDES UV PROTECTION FOR INDOOR AND OUTDOOR GRAPHICS (UP TO 3 YEARS)
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A SCUFF-RESISTANT FINISH IS REQUIRED
- CAN BE COMBINED WITH DRYTAC'S FLOORTAC™ PRINT MEDIA TO CREATE A SLIP-RESISTANT INDOOR FLOOR GRAPHIC DURABLE FOR UP TO 6 MONTHS.

*PROTAC SCUFFGUARD IS NOT SUITABLE FOR OUTDOOR FLOOR GRAPHIC APPLICATIONS.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Textured Monomeric Calendared PVC
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side White Kraft

PRODUCT CHARACTERISTIC

Film Thickness	6 mil (150µ)
Adhesive Layer	0.8 mil (20µ)
UV Protection	Yes
Outdoor Durability	5 Years*
Slip Rating	R10 (DIN 51130) Moderate Slip Potential; Dry: 62; Wet: 31 (EN 13036-4)
Fire Rating	Class 0 (BS 476 Part 6 and 7)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Application Temperature	>41°F (5°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com